



NOTE:

IT IS IMPORTANT THAT THE CONCAVE WASHERS (E) BE SNUGLY NESTED INTO THE CERAMIC BUSHING (F), BETWEEN NUTS (C & D). HOWEVER, NUT MARKED (D) SHOULD BE FINGER TIGHTENED ONLY IN ORDER TO PREVENT DAMAGE TO BUSHING (F).

TO SECURE RING TERMINAL, HOLD (D) NUT WITH SMALL WRENCH [ENSURING TENSION ON CERAMIC BUSHING DOES NOT CHANGE] AND TIGHTEN (C) NUT AGAINST RING TERMINAL.

COMPONENTS

- A = #10-24X1.75 STAINLESS STEEL BOLT (1)
- B = #10 SS FLAT WASHER (2)
- C, D = 10-24 SS NUT (3)
- E = #10 SS CONCAVE WASHER (2)
- F = SMALL CERAMIC BUSHING (1)
- G = BUSHING RETAINER CLIP (1)
- H = #10STUD/12-10AWG HI-TEMP RING TERMINAL (1)

		INTEK		
		Prop. No. TERM-BOLT-ASM Part Name: TERMINAL BOLT ASSEMBLY Date:	Qty: N.T.S. Tolerance: X = +/- .0625" Y = +/- .0315" Z = +/- .0156" L = +/- 1 Deg.	
PROPRIETARY AND CONFIDENTIAL USE ONLY! This document and all accompanying information is proprietary and confidential, belonging to the sender for the sole purpose of communicating design concepts created by Intek Corporation. Disclosure, electronic storing, copying or distribution is strictly prohibited!				
Designed By	ENGINEERING	Drawn By	L. RINATI	
Date	06-19-13	Approved By		
REVISIONS	No.	Date	By	Description
	A	5-26-17	RJB	Corrected component definitions.